

Specifications

Solid Plastic Vanities

4.17

Solid Plastic Vanities

Part 1 - General

1.01 Work Included

A. The restroom vanities shall be high-density polyethylene (HDPE) polymer as manufactured by **ASI Accurate Partitions**, Burr Ridge, Illinois.

B. Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

1.02 Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of vanities.

Part 2 – Product

2.01 Vanity, Back Splash, Side Splash, Apron and Support – Shall be 1” thick, HDPE that is water-resistant and non-absorbent.

2.02 Material – The HDPE material shall have homogeneous color throughout with ¼” machined edges.

2.03 Construction – Vanity top shall be standard width of 24” with a maximum length of 120” for single piece. Apron, back splash, and side splash shall be a standard height of 4” and have a maximum length of 120”.

2.04 Hardware – HDPE vanity supports shall be secured to the vanity top and wall by anodized aluminum angles. The vanity top shall also be secured to the wall by anodized aluminum angles.

Part 3 – Execution

3.01 Installation – Shall be installed in accordance to the **ASI Accurate** installation instructions with vanities rigid, straight and plumb.

3.02-Warranty – **ASI Accurate Partitions** Guarantees its solid plastic HDPE material against breakage, corrosion and delamination for 25 YEARS from the date of receipt by the customer. If material is found defective during that period, the materials shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.